



These Interfaces are used to “translate” or convert multiplex lighting protocols. Users can select from the following input and output protocols:

- DMX512/1990 and DMX512-A
- AMX192 - all versions
- Kliegl K96 & K100
- Colortran CMX & D192
- Electro Controls EC Mux
- Micro-Plex 1 & 2
- Strand D54
- AVAB - 240 & 252 channels

FEATURES

- Multiple protocol support in a single unit
- Intuitive configuration with backlit menu driven LCD display
- Most multiplex protocols supported
- Security lockout function
- Input & output diagnostic functions
- Output protocol customization capability

MODEL DESCRIPTION

8680	Tabletop <i>Ultimate</i> Converter, North America <i>4 & 5 pin XLR input/output connectors</i>
8681	Tabletop <i>Ultimate</i> Converter, Europe <i>3 & 5 pin XLR input/output connectors</i>
8802	19" Rack Mount Kit

SPECIFICATIONS

Power Supply:	Universal 100-240VAC, 50/60 Hz, 0.2A
Size:	10.15 x 1.75 x 7.0 in. (258 x 44 x 178mm)
Input & Output Configuration:	Keypad and 16 character, two line backlit LCD
Enclosure:	Aluminum with black powder epoxy



The Only Sure Thing In Show Business
www.pathwayconnect.com